



Meltblown, Sonic Bonded Roll in Maintenance

190MBGRB



Meltblown | Maintenance | Roll | Sonic Bonded

Basis weight: 190 gsm*

Absorbency: 242 Litres | 53 US Gallons of oil**
174 Litres | 38 US Gallons of water**



Base Fibre: Polypropylene

Meltblown

Product Code	Colour	Weight	Format	Size cm (inches)	Recycled Content	Units/Case	Weight/Case***	LTL/Pallet	FTL/Pallet
Maintenance									
190MBGRB	Grey	190 gsm	Roll	76 cm x 91 m (30" x 300')	0%*	1	12.8 kg (28.3 lbs)	36	42

Sonic Bonded meltblown

Single Layer of meltblown polypropylene fibres with bond points



This product is in a Maintenance format



This is one of our lower weight products

Description

This roll is the lowest cost lower weight Maintenance meltblown rolls available. The roll is made from one layer of meltblown which is sonically bonded together. The bonding makes the pad less linty when compared to un-bonded meltblown. Very even structure helps to contribute to its good absorbency capacity. Being the industry standard, its all-round performance is average but it is very versatile.

All the rolls are perforated down their length, every 19 cm (7.5") and across the roll every 50 cm (20") at no additional cost.

Key features

- The pad is made from one layer of meltblown that is sonically bonded together.

- Good value and reliable performance.
- Made from high quality polypropylene..

Application

An economical choice for everyday Maintenance situations. An excellent go to product for lighter duty indoor MRO tasks. Because the pad is Maintenance, only use indoors.

Notes

- Fire retardant as per ASTM 726
- Ensure that disposal of these sorbents complies with all regulations

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

Related Regulations	Description
29CFR 1910.22(a)(2)	"The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition."
29CFR 1910.120(j)(1)(vii)	"...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur."
29CFR 1910.107(g)(2)	"All spraying areas shall be kept as free from the accumulation of deposits of combustible residues as practical."