



# Meltblown, Sonic Bonded Split Roll in Oil only

286MBWSRB



Meltblown | Oil only | Split Roll | Sonic Bonded

**Basis weight:** 286 gsm\*

**Absorbency:** 76 Litres | 17 US Gallons of oil\*\*



**Base Fibre:** Polypropylene

## Meltblown

| Product Code | Colour | Weight | Format     | Size cm(inches)           | Recycled Content | Units/Case | Weight/Case***    | LTL/Pallet | FTL/Pallet |
|--------------|--------|--------|------------|---------------------------|------------------|------------|-------------------|------------|------------|
| Oil only     |        |        |            |                           |                  |            |                   |            |            |
| 286MBWSRB    | White  | 286gsm | Split Roll | 38 cm x 46 m (15" x 150') | 0%*              | 2          | 4.9 kg (10.7 lbs) | 36         | 42         |

## Sonic Bonded meltblown

Single Layer of meltblown polypropylene fibres with bond points



*This product is in an Oil only format*



*This is one of our heavier weight products*



*We recommend this product for removing oil on land*

### Description

This split roll is the lowest cost heavier weight Oil only meltblown rolls available. The split roll is made from one layer of meltblown which is sonically bonded together. The bonding makes the pad less linty when compared to un-bonded meltblown. Very even structure helps to contribute to its good absorbency capacity. Being the industry standard, its all-round performance is average, but it is very versatile.

The rolls are perforated down their length, every 19 cm (7.5") and across the roll every 50 cm (20") at no additional cost.

### Key features

- The roll is made from one layer of Meltblown that is sonically bonded together.
- Good value and reliable performance.
- Made from high quality polypropylene.

\* Basis weights and recycled content are ± 5%

\*\* Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

\*\*\* Weight per case ± 0.5 kg/lbs.

### Application

An economical choice for everyday Oil only situations. An excellent go to product for lighter duty outdoor Oil only tasks. Because the roll is Oil only, use mostly outdoors.

### Notes

- Fire retardant as per ASTM 726
- Ensure that disposal of these sorbents complies with all regulations.

## Compliance

| Related Regulations       | Description  |
|---------------------------|--|
| 29CFR 1910.22(a)(2)       | "The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition."                             |
| 29CFR 1910.120(j)(1)(vii) | "...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur." |
| 29CFR 1910.107(g)(2)      | "All spraying areas shall be kept as free from the accumulation of deposits of combustible residues as practical."                 |