



Meltblown, Fine Fibre Pads in Maintenance

190XMBGPF



Meltblown | Maintenance | Pads | Fine Fibre

Basis weight: 190 gsm*


Absorbency: 134 Litres | 29 US Gallons of oil**
95 Litres | 21 US Gallons of water**

Base Fibre: Polypropylene

Meltblown

Product Code	Colour	Weight	Format	Size cm (inches)	Recycled Content	Units/Case	Weight/Case***	LTL/Pallet	FTL/Pallet
Maintenance									
190XMBGPF	Grey	190gsm	Pads	40 cm x 50 cm (16" x 20")	0%*	200	7.6 kg (16.8 lbs)	36	42

Fine Fibre meltblown




This product is in a Maintenance format



This is one of our lighter weight products



Pad size is 40 cm x 50 cm (16" x 20")



Description

This lighter weight Maintenance fine fibre pad is among our best and most expensive meltblown pads. Although not as absorbent as our Ultraclean™ family, this product category is the industry standard when looking for a high end meltblown absorbent. Ideal when you need a fast wicking highly chemical resistant meltblown product.

Precision-engineered and manufactured using state of the art Exxon technologies to maximize durability and fast wicking.

Key features

- The sorbent is made up of three layers sonically bonded together.
- Top and bottom layers are made from micro fibres of densely woven polypropylene.

- Core is made from a high loft polypropylene.
- Pads are boxed making individual pad shipment economical.
- Low linting.
- Pads are perforated down their centre.
- High chemical resistance.

Application

Ideal when you need a fast wicking meltblown product to quickly clean up larger spills. Its soft cover sheets make it a good choice to absorb liquids from hard to reach places.

Notes

- Fire retardant as per ASTM 726
- Ensure that disposal of these sorbents complies with all regulations

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

Related Regulations	Description
29CFR 1910.22(a)(2)	"The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition."
29CFR 1910.120(j)(1)(vii)	"...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur."
29CFR 1910.107(g)(2)	"All spraying areas shall be kept as free from the accumulation of deposits of combustible residues as practical."