



Dash Bin 120 Litre Oil only Spill Kit

SK-O120DASH



Spill kit | 120 Litre | Oil only | Dash Bin

Basis weight: -

Absorbency: 120 Litres | 26.4 US Gallons of oil**

Base Fibre: Cellulose




Coldform™

Product Code	Colour	Weight	Format	Size cm(inches)	Recycled Content	Units/Case	Weight/Case™	LTL/Pallet	FTL/Pallet
SK-O120DASH	White	286 gsm	Spill Kit	-	60%*	1	-	-	-


120 Litre Spill Kit in a Dash Bin

Spun-bond top cover
Coldform™ core



120 Litre Dash Bin Spill kits contain:

- 60 x heavy weight pads
- 5 x 1.2 m socks
- 4 x 46 cm x 46 cm pillows
- 5 x waste disposal bag and ties



This product is in an Oil only format

Description

Contained in a rugged two wheeled bin with hinged lid, this spill kits will be ideal for locations where a quantity of sorbents need to be taken to the site of a spill at a moments notice. A further selling point of these kits is the ability to put all the bagged sorbents back in the bin for removal.

All these spill kits feature a combination of pads, socks and pillows that will contain and recover a 120 litre spill as well as the basic equipment needed to handle the clean up process. These kits can be adapted or have branding added. Please note the PPE shown is not included but can be specified if required.

This kit contain Coldform™ cellulose absorbents. The Oil only Coldform™ pads are unique in the fact that one side is no lint, and very durable and the other side is soft and absorbent.

Notes

- Fire retardant as per ASTM 726
- Ensure that disposal of these sorbents complies with all regulations.

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

Related Regulations	Description
29CFR 1910.22(a)(2)	"The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition."
29CFR 1910.120(j)(1)(vii)	"...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur."
29CFR 1910.107(g)(2)	"All spraying areas shall be kept as free from the accumulation of deposits of combustible residues as practical."